

MATERIAL SAFETY DATA SHEET
TRADE NAME: E-Z-1 SYNTHETIC PENETRATING LUBRICANT

(Page 1 of 2)

E-Z-1 CORPORATION, 3500 NORTH HARRISON, SHAWNEE, OK 74804
PHONE: 405-275-8110

I. E-Z-1 Corporation; 3500 N. Harrison, Shawnee, Ok. 74804

II. HAZARDOUS INGREDIENTS

HAZARD DETERMINATION: MATERIAL IS NOT HAZARDOUS AS DEFINED BY OSHA HAZARD COMMUNICATION STANDARD, 29CFR1910.1200.

NON-HAZARDOUS INGREDIENT: 40 TO 70 % SYNTHETIC HYDROCARBON
-CAS #68515-33-3

5 TO 25 PERCENT METALLIC SALTS - CAS# MIXTURE (TRADE SECRET)
COMPONENTS OF THIS MATERIAL ARE NOT KNOWN TO BE HAZARDOUS.
5 TO 30 PERCENT SYNTHETIC HYDROCARBON - CAS# (TRADE SECRET)
THIS MATERIAL IS NOT KNOWN TO BE HAZARDOUS.

III. PHYSICAL DATA

BOILING PT.: 650-790 °F

SPECIFIC GRAVITY: .895

VAPOR DENSITY: N/A

% VOLATILE BY VOL.: NIL

APPEARANCE/ODOR: LT. ORANGE BROWN

MELTING POINT: MINUS 110 ° F

VAPOR PRESSURE: NIL

SOLUBILITY IN H2O: NIL

EVAPORATION RATE: N/A

PH: NEUTRAL

VOLATILE ORGANIC CONTENT: 0 GM./LITER

IV. FIRE AND EXPLOSION DATA

FLASH PT. (TEST METHOD): 380 ° F COC

AUTO IGNITION TEMP.: 555 ° F

FLAMMABLE LIMITS IN AIR: N/A

EXTINGUISHING MEDIA: USE WATER SPRAY, DRY CHEMICAL, FOAM, OR CARBON DIOXIDE.

SPECIAL FIRE FIGHTING PROCEDURES: WATER OR FOAM MAY CAUSE FROTHING. USE WATER TO KEEP CONTAINERS COOL. WATER SPRAY MAY BE USED TO FLUSH SPILLS.

UNUSUAL FIRE/EXPLOSION HAZARD: PRODUCTS OR COMBUSTION MAY CONTAIN CARBON MONOXIDE, CARBON DIOXIDE, OR OTHER MATERIALS. *DO NOT ENTER ENCLOSED OR CONFINED AREA WITHOUT PROPER PROTECTIVE EQUIPMENT, INCLUDING RESPIRATORY EQUIPMENT.

V. HEALTH HAZARD INFORMATION

INHALATION: NO VOLATILES, INHALATION IS UNLIKELY ROUTE. ACUTE INHALATION IN RATS LC50 MG/LITER, GREATER THAN 2.0 (NON TOXIC)

SKIN CONTACT: REPEATED EXPOSURE CAN CAUSE IRRITATION. CLOTHING (DRY) AND GLOVES (IMPENETRABLE). WASH OFF WITH SOAP AND WATER. PRIMARY SKIN IRRITATION IN RABBITS: AVE SCORE: 1.88 (MILD IRRITANT)

SKIN ABSORPTION: UNLIKELY. USE PROTECTIVE GEAR DURING CONTINUED OR EXTREME EXPOSURE.

EYE CONTACT: CAN CAUSE IRRITATION. USE SAFETY GLASSES AT ALL TIMES, GOGGLES WHEN HANDLING IN OVERHEAD OR WHEN AGITATING. EYE IRRITANT IN RABBITS.

WASHED – MILD IRRITANT. UNWASHED – MINIMAL IRRITANT.

INGESTION: ORAL LD50 (RAT) AT 5000 MG/KG. NO DEATHS.

VI. EFFECTS OF OVEREXPOSURE

ACUTE OVEREXPOSURE: POTENTIAL SKIN AND EYE IRRITANT

CHRONIC OVEREXPOSURE: PRODUCT MAY CAUSE IRRITATION TO EYES, LUNGS, OR SKIN AFTER PRODUCT OR REPEATED EXPOSURE. OVER EXPOSURE MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION.

MATERIAL SAFETY DATA SHEET
TRADE NAME: E-Z-1 SYNTHETIC PENETRATING LUBRICANT
(Page 2 of 2)

VII. EMERGENCY AND FIRST AID PROCEDURES

EYES: WASH WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, CONSULT PHYSICIAN.

SKIN: USE PROTECTIVE CLOTHING FOR SENSITIVE SKIN. WASH WITH SOAP AND WATER TO REMOVE.

INHALATION: REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT.

INGESTION: IF LARGE AMOUNTS ARE INGESTED, DO NOT INDUCE VOMITING. CONSULT PHYSICIAN AS GASTRIC LAVAGE MAY BE INDICATED.

VIII. REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY: GENERALLY STABLE, KEEP AWAY FROM HEAT SOURCES AND OPEN FLAME.

INCOMPATIBILITY: KEEP AWAY FROM STRONG OXIDIZERS.

HAZARDOUS DECOMPOSITION PRODUCTS: GENERALLY NONE, EXCEPT AS CARBON MONOXIDE DURING INCOMPLETE COMBUSTION. CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION: NONE

IX. DISPOSAL, SPILL, OR LEAK PROCEDURES

AQUATIC TOXICITY: NONE KNOWN

WASTE DISPOSAL METHOD: USE ABSORBATIVE MATERIAL AND DISPOSE AT PROFESSIONAL DISPOSAL COMPLYING WITH STATE, FEDERAL, AND LOCAL REGULATIONS.

IF MATERIAL IS SPILLED OR RELEASED: CONTAIN SPILL IMMEDIATELY IN SMALLEST AREA POSSIBLE. SOAK UP AND DISPOSE IN PROFESSIONAL DISPOSAL FASHION. KEEP OUT OF SEWERS OR BODIES OF WATER.

NEUTRALIZING CHEMICALS: NONE INDICATED

X. SPECIAL PROTECTIVE INFORMATION

VENTILATION: NORMAL SHOP VENTILATION

RESPIRATORY: NONE NORMALLY REQUIRED EXCEPT AS NOTED IN SECTION IV*.

EYE: ALWAYS WEAR SAFETY GLASSES. CHEMICAL GOGGLES IF DANGER OF SPLASH OR DRIP EXISTS.

GLOVES: RECOMMEND IMPERVIOUS TYPE.

HMS RATING: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0, PERSONAL PROTECTION A.

XI. SPECIAL PRECAUTIONS

NOT LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN BY NTP, IARC, OR OSHA.

HANDLING OR STORAGE REQUIREMENTS: D.O.T. LABEL: NOT REGULATED
OSHA LABEL: NOT REGULATED

PRODUCT IS CLASS III B COMBUSTIBLE

LIQUID PER NFPA CODE NO. 30-1984 STORE/HANDLE ACCORDINGLY.

MSDS UPDATED: 01 JANUARY 2006

RESPONSIBLE FOR MSDS: JOHN TYLER INDA: DIRECTOR R/D, PHONE (405)275-8110

E-Z-1 CORPORATION

FAX (405)275-8114
SALES@E-Z-1.COM